

1Z0-822^{Q&As}

Oracle Solaris 11 Advanced System Administration

Pass Oracle 1Z0-822 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.certbus.com/1z0-822.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Oracle Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Examine the following command:

ipadm create-addr -T static -a 192.168.1.112/26 net0/v6

Which two statements are true?

- A. The interface is plumbed.
- B. The interface is marked down.
- C. The netmask value is ffffffc0.
- D. The link local IPv6 address fe80::112 is created.
- E. Multicast datagrams are not enabled on this interface.

Correct Answer: CD

QUESTION 2

The default route for the NCP static is changed with the following command sequence:

```
netadm list
          PROFILE
                          STATE
TYPE
                          disabled
           Automatic
ncp
           start state
                          disabled
ncp
ncp
           Static
                          online
                          online
           net0
ncu:phys
                          online
           net0
ncu:ip
loc
                          online
           aces
                          offline
loc
           Automatic
           NoNet
                          offline
                          disabled
loc
           User
# netcfq
netcfg> select ncp Static
netcfg:ncp:Static> select ncu ip net0
netcfg:ncp:Static:ncu:net0> set ipv4-default-route=192.168.30.1
netcfg:ncp:Static:ncu:net0> verify
netcfg:ncp:Static:ncu:net0> commit
netcfg:ncp:Static:ncu:net0> exit
```

When does the entered route take effect?

- A. after the set command
- B. after the verify command
- C. after the commit command



- D. after the exit command
- E. after enabling the location user (command not shown)

Correct Answer: C

QUESTION 3

Consider the following ZFS configuration:

NAME	USED	AVAIL	REFER	MOUNTPOINT
rpool/export	436M	9.21G	284M	/export
rpool/export/home	152M	9.21G	35K	/export/home
rpool/export/home/curly	35K	9.21G	35K	/export/home/curly

You have created snapshots of the homo directories which are as follows:

NAME rpool/export/home@11.28.12	USED 0	AVAIL	REFER 32K	MOUNTPOINT
rpool/export/home/curly@11.28.12	0	-	802K	-

You have another storage pool named bpool on the same system. You use the following command to store the snapshots in this pool:

zfs send rpool/export/home@11.28.12 | zfs recv f bpool@11.28.12

What will be created in the pool bpool as a result of this operation?

- A. bpool/export/home/ bpool/export/home/curly
- B. bpool/export/home/ bpool/export/home/curly bpool/export/home@12.25.11
- C. bpool/export/home/ bpool/export/home/curly bpool@12.25.11
- D. bpool/curly bpool/curly@12.25.11
- E. bpool/curly
- F. bpool/curly bpool@12.25.11

Correct Answer: A

QUESTION 4

Which network component is the default target for IPMP probe-based Failure detection?

- A. the default router
- B. any nongateway system on the same subnet
- C. any group interface with a test address



D. the first responder to the in.mpathd broadcast request

Correct Answer: A

QUESTION 5

You have a server that has two zones configured. These zones use the pool named pool_zones. Examine the following configuration information:

	peol pool zones				
	int	pool.s	ys id 1		
	boolean	Contraction of the second s	active t		
	boolean	pool.			
	string poo				
	int		mportan	ce 1	
	string poo				
	pset				
224					
	pset pset_zones				
	int	pset.	sys_id 1		
	boolean	pset.	default	false	
	uint	pset.	min 2		
	uint	pset.	nax 2		
	string pse			on	
	uint	pset.			
	uint	pset.	size 0		
	string pse	t.comment			
2.2.2					
	a state of the sta	and a second			
zone:	oll1-server:~# p	rctl -n z	one.cpu-	-shares -1 zon	0 21
NAME	PRIVILEGE	VALUE		ACTION	In the second
	pu-shares	VALUE	FLAG	ACTION	RECIPIEN
aune co		46			
******	usage privileged	40		none	

The system has four CPUs. Assume that both zones are under heavy load. Examine the following partial output:

root@so	5111-se	rver:-	prst	tat -Z			
ZONEID 0 5 4	NPROC 109 16 29	2583M 94M	742M 961M	16% 22.2%	TIME CPU 0:17:42 0:01:15 0:00:27	2.5% xxx%	zl

- Which option describes the values you would expect to see for the CPU field for the zones?
- A. approximately 40% for z1 and approximately 60% for z2
- B. approximately 60% for z1 and approximately 40% for z2
- C. approximately 20% for z1 and approximately 30% for z2
- D. approximately 30% for z1 and approximately 20% for z2



E. approximately 25% for z1 and approximately 25% for z2

Correct Answer: A

QUESTION 6

Which vmstat field output indicates the effort the system is making to find memory for future processes?

A. re

B. sr

C. free

D. fr

Correct Answer: A

QUESTION 7

You created a virtual network of three zones.

One network hosts a web server.

Another hosts an application server used by the web server.

The third zone host a video streaming application.

You already configured a flow to prioritize the video traffic over the web server traffic. You now need to continuously monitor the flow.

Which tool must you use to gather the flow data?

- A. the system activity reporter (SAR)
- B. extended accounting
- C. the flowstat command
- D. the kstat utility

Correct Answer: A

QUESTION 8

Which sequence of commands will create a virtual network interface?



```
A) dladm create-vnic -l net0 vnic0
ipadm create-ip vnic0
ipadm create-addr -T static -a 192.168.1.101/24 vnic0/v4
B) dladm create-vnic -l vnic0 net0
ipadm create-ip net0
ipadm create-addr -T static -a 192.168.1.101/24 net0/v4
C) dladm create-vlan -l vnic0 -v 111 net0
ipadm create-ip vnic0
ipadm create-addr -T static -a 192.168.1.101/24 vnic0/v4
D) dladm create-vnic -l net0 vnic0
ipadm create-addr vnic0
ipadm create-addr vnic0
ipadm create-ip -T static -a 192.168.1.101/24 net0/v4
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Correct Answer: A

QUESTION 9

You have assigned rights profiles directly to the uses frank and now you want to add another profile. Which command enables you to list profiles directly assigned to frank?

- A. userattr profiles frank
- B. profiles p frank
- C. useratter p frank
- D. profiles frank

Correct Answer: B

QUESTION 10

You administer an Oracle Solaris 11 server. You created an IPS repository and set the pkg publisher origin. You did not configure the pkg/service service. What type of access have you provided for your now repository?

- A. a file interface repository
- B. a local host-only repository
- C. a testing-interface repository



D. a pkg.depotd configured interface

Correct Answer: B

QUESTION 11

Your organization uses NFS to share data from Oracle Solaris servers to Oracle Solaris clients. For the nfsmapid daemon to work properly the client and server must be on the same domain. Select the location that has the highest precedence when the nfsmapid daemon searches for a domain name.

- A. the nfsmapid_domain parameter in the mapid SMF service.
- B. the nfsmapid_domain parameter in the /etc/default/nfs file
- C. the domain name in the /etc/default/domainname file, if it exists.

D. a_nfsv4idmapdomain TXT record found by the configured domain name servers

Correct Answer: C

QUESTION 12

You must configure your server to use IPMP with probe based failure detection enabled. Which statement is a valid constraint or feature that applies to this requirement?

- A. Link-based detection is supported only on Genetic Land Driver version 2 (GLDv2)-complaint NICs.
- B. GLDv2 NICs are not supported in Oracle Solaris 11.
- C. GLDv3 NICs configured for link based detection by default.
- D. You must first disable link based detection before configuring probe-based failure detection.

Correct Answer: D

QUESTION 13

Which two statements describe the capabilities of the Distribution Constructor?

- A. ISO images for use with the Automated Installer (AI) can be created.
- B. Bootable USB images can be created for SPARC and x86 architectures.
- C. A single installation server can be used to create ISO imager, for SPARC and x86 architectures.
- D. Checkpoints are used to pause the build, thereby allowing the running of a script to modify the resulting ISO image.
- E. A single installation server can be used to create ISO images for Solaris 10 and Solaris 11.0 operating systems.

Correct Answer: BE



QUESTION 14

You need to make a permanent modification to a machine\\'s naming service. You need to change naming service from files to LDAP. Which two alternative methods would accomplish this task?

A. Modify the existing /etc/nsswitch.conf file and execute: # nscfg import -?name-service/switch

B. Modify the existing /etc/nsswitch-conf file and execute: # netcfg import name-service/switch # svcadm refresh name-service/switch

C. Modify the existing /etc/nsswitch.conf file and execute: # svcadm restart milestone/self-assembly

D. Use the netcfg command to modify the location profile for the DefaultFixad network configuration profile.

E. Use the svccfg command to set config/* properties in the name-service/switch service: # svcadm refresh name-service/switch # svcadm restart name-service/switch

Correct Answer: BE

QUESTION 15

While examining an Oracle Solaris 11 system, you discover an unfamiliar ELF binary in the /usr/bin directory. You want to know which package installed the binary. Which pkg subcommand should you use to identify the package, based on the absolute path to the binary?

A. pkg info

B. pkg list

- C. pkg search
- D. pkg contents

Correct Answer: D

Latest 1Z0-822 Dumps

1Z0-822 Study Guide

1Z0-822 Braindumps