

ACE-A1.2^{Q&As}

Arista Certified Engineering Associate

Pass Arista ACE-A1.2 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.certbus.com/ace-a1-2.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Arista
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

What must be active on the VMware side in order for EOS to have visibility into vNIC counters?

- A. vSwitches must be used.
- B. Distributed switches must be used.
- C. vSphere must be used.
- D. vNIC counters are not supported in VMTracer.

Correct Answer: A

QUESTION 2

What is the command to make sure that all installed extensions are loaded when the switch reboots?

- A. install extensions permanent
- B. boot installed-extensions
- C. copy extensions: boot-extensions:
- D. copy installed-extensions boot-extensions

Correct Answer: D

Reference: <https://eos.arista.com/packaging-and-installing-eos-extensions/>

QUESTION 3

If you have an Arista switch with SFPs, which command will show the temperature of those SFPs?

- A. show interfaces transceiver
- B. show interfaces
- C. show interfaces status
- D. show sfp monitor

Correct Answer: A

Reference: <https://www.arista.com/ko/um-eos/eos-section-10-6-ethernet-configuration-commands>

QUESTION 4

Which of the following are valid commands on EOS 4.14? (Choose three.)

- A. show run all
- B. show run diffs
- C. show run sanitized
- D. show run section

Correct Answer: ABC

Reference: <http://www.nycnetworkers.com/study-tips/arista-eos-cli-cheat-sheet/>

QUESTION 5

How is LANZ enabled on switches that support it?

- A. With the management lanz command, followed by the no shutdown command.
- B. With the queue-monitor enable command.
- C. With the lanz enable command.
- D. With the queue-monitor length command.

Correct Answer: D

Reference: [https://www.arista.com/assets/data/pdf/user-manual/um-eos-4172f/Chapters/um-eos4172f_Latency%20Analyzer%20\(LANZ\).pdf](https://www.arista.com/assets/data/pdf/user-manual/um-eos-4172f/Chapters/um-eos4172f_Latency%20Analyzer%20(LANZ).pdf) (page 3)

QUESTION 6

What command configuration mode enabled you to connect to an Arista Switch via HTTPS for services such as Tap Aggregation?

- A. management web secure
- B. management web https enable
- C. management web commands
- D. management api http-commands

Correct Answer: D

Reference: <https://eos.arista.com/arista-eapi-101/>

QUESTION 7

What is the command to set the switch to use EOS 4.15.1F.swi the next time it reloads?

- A. boot system flash:EOS-4.15.1.swi

- B. boot system 4.15.1F.swi
- C. boot system flash:/EOS-4.15.1F.swi
- D. boot system flash EOS-4.15.1F.swi

Correct Answer: C

QUESTION 8

True or False: XMPP Management is enabled by default.

- A. TRUE
- B. FALSE

Correct Answer: B

Reference: <https://www.arista.com/en/um-eos-4172f/eos-section-2-5-session-managementcommands#ww1129609>

QUESTION 9

True or False: When ZTP has been placed in cancel mode, you must issue the write memory command to prevent ZTP from triggering again.

- A. TRUE
- B. FALSE

Correct Answer: B

QUESTION 10

What is the name of the Arista EOS feature that allows you to view historical ARP table changes?

- A. Event Manager
- B. Event Monitor
- C. Event Trigger
- D. Event History

Correct Answer: B

Reference: <https://www.arista.com/en/um-eos/eos-section-5-5-event-monitor>

QUESTION 11

Arista Switches employ which of the following?

- A. Merchant silicon ASICs
- B. Custom ASICs
- C. Both
- D. Arista switches do not use ASICs

Correct Answer: A

QUESTION 12

What will the following command do?

```
show event-monitor arp | grep 10.100.100.6
```

- A. Show all the historical ARP entry changes on the remote Arista switch located at IP address 10.100.100.6
- B. Show all the event-monitors for a switch that has an ARP address matched to the IP address 10.100.100.6
- C. Show all historical ARP entry changes that contain the IP address 10.100.100.6
- D. This is not a valid command

Correct Answer: C

QUESTION 13

Which of the following are valid interface named in EOS? (Select three)

- A. Ethernet 1
- B. FastEthernet 38
- C. vxlan 1
- D. Vlan 101

Correct Answer: ACD

QUESTION 14

In EOS, which of the following statements is the shortest acceptable abbreviation for entering global configuration mode?

- A. conf
- B. con
- C. config
- D. conf t

Correct Answer: A

```
Arista1#  
Arista1#con  
% Ambiguous command  
Arista1#  
Arista1#conf  
Arista1(config)#_
```

QUESTION 15

Which command below is valid to use as a way to verify the status of the MLAG peer-link?

- A. show mlag
- B. show mlag interface
- C. show mlag peer-link
- D. show mlag detail

Correct Answer: A

Reference: https://eos.arista.com/mlag-basic-configuration/#Verify_spanning-tree_on_both_MLAG_peers

[Latest ACE-A1.2 Dumps](#)

[ACE-A1.2 Study Guide](#)

[ACE-A1.2 Exam Questions](#)