

# E20-351<sup>Q&As</sup>

Storage Attached Network (SAN) Specialist Exam

**Pass EMC E20-351 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.certbus.com/e20-351.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



#### QUESTION 1

What is required for accessing SAN Advisor remotely?

- A. EMC Control Center SAN Advisor client must be installed on the local host.
- B. EMC Control Center SAN Advisor service must be running on the SAN AdvisorServer.
- C. EMC SAN Advisor Host Agent must be running on the local host.
- D. EMC SAN Advisor Remote Access Agent must be running on the SAN AdvisorServer.

Correct Answer: B

---

#### QUESTION 2

What are the device special files naming convention in a Solaris environment?

- A. `./PHYSICALDRIVE#`
- B. Block Device is `/dev/dsk/c##d#` and Character Device is `/dev/rdisk/c##d#`
- C. Block Device is `/dev/dsk/c##d#s2` and Character Device is `/dev/rdisk/c##d#s2`
- D. Block Device is `/dev/hdisk#` and Character Device is `/dev/rhdisk#`

Correct Answer: C

---

#### QUESTION 3

A data center contains the equipment and software required for a three-tier web application: a public-facing web server and an Oracle database, both of which are connected to storage via a SAN. The management server that hosts all required management applications is not connected to the SAN. What is a security best practice that should be established?

- A. Allow all support personnel to log in to the application they are responsible for with fullaccess for faster problem resolution
- B. Connect the management server to the SAN to allow for faster problem resolution
- C. Only log the network traffic of the public-facing web server
- D. Use encrypted or key exchange protocols to ensure that passwords cannot be sniffed

Correct Answer: D

---

#### QUESTION 4

How many active zone sets are assigned to an individual VSAN at one time?

- A. unlimited
- B. 1
- C. 2
- D. 2048

Correct Answer: B

---

#### QUESTION 5

FashionStar Inc. is implementing an SRDF over IP solution. It wants to merge two existing fabrics in order to complete this solution. Which technology should FashionStar use?

- A. FCIP
- B. iFCP
- C. iSATA
- D. iSCSI

Correct Answer: A

---

#### QUESTION 6

Which command is used to verify FC Routing Services License Installed for FCIP on a Connectrix B-Series switch?

- A. licenseshow
- B. show switch
- C. showlicense
- D. switch show

Correct Answer: A

---

#### QUESTION 7

A customer has a SAN made up of one DMX, one MDS 9506, and 20 Solaris hosts. They will be installing Control Center in the environment. In order to use Control Center to perform masking operations on the DMX, which agents must be present in the Control Center environment?

- A. FCC Agent, SDM Agent
- B. FCC Agent, Storage Agent for Symmetrix
- C. SDM Agent, Storage Agent for Symmetrix

D. Sun Agent, Storage Agent for Symmetrix

Correct Answer: C

---

#### QUESTION 8

Click the Exhibit button. Which MDS switch will become the principal switch, when VSAN 5 attempts to merge? \*\*Exhibit Missing\*\*

- A. MDS A
- B. MDS B
- C. Neither, they will not merge due to different domains
- D. Neither, they will not merge due to different priorities

Correct Answer: A

---

#### QUESTION 9

What does the s# represent in the device special file format of c##d#s#?

- A. LUN number
- B. SCSI controller number
- C. Slice partition number
- D. Target ID number

Correct Answer: C

---

#### QUESTION 10

An ISL is plugged in to the first port of the first quad on a 32-port switching module (fc1/1). For redundancy, a second ISL will be added. If no other ports are being used on the switching module, which port should be used for the second ISL?

- A. fc1/2
- B. fc1/3
- C. fc1/4
- D. fc1/5

Correct Answer: D

---

**QUESTION 11**

For which operating systems are the SCSI-3 (SC3) bit set on a Symmetrix FA port?

- A. Used for Heterogeneous FA Port Sharing/IBM AI with FC 6227, 6228, 6239/VMware
- B. Used for Solaris only
- C. Used for Windows/Solaris/AIX
- D. Used for Windows/Solaris/HP-UX

Correct Answer: A

---

**QUESTION 12**

To save the configuration of a B-Series switch, which command is used?

- A. backupConfig
- B. configDownload
- C. configUpload
- D. firmwareDownload

Correct Answer: C

---

**QUESTION 13**

In an iSCSI client-server architecture, what are clients of a SCSI interface called?

- A. Client
- B. Device server
- C. Initiator
- D. Target

Correct Answer: C

---

**QUESTION 14**

Which connection is used to group nodes from physically different fabrics together in a BSeries environment?

- A. iSAN
- B. LSAN
- C. MSAN

D. VSAN

Correct Answer: B

---

#### QUESTION 15

An HP-UX host is zoned to a Symmetrix DMX. The HBAs are logged in to the fabric and the host sees the VCMDB device. Why would the host not show in the Symmetrix login history table as logged in?

- A. HP-UX HBA will not log in with a Sun Solaris server attached to the same FA
- B. HP-UX HBA will not log in with an AIX server attached to the same FA
- C. HP-UX HBAs logs out of the FAs if there is no activity
- D. HP-UX HBAs never log in to FA

Correct Answer: C

[E20-351 Practice Test](#)

[E20-351 Exam Questions](#)

[E20-351 Braindumps](#)