

E20-616^{Q&As}

Symmetrix Installation and Troubleshooting Specialist

Pass EMC E20-616 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.certbus.com/e20-616.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by EMC Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





A customer plans to upgrade an existing four-Engine Symmetrix VMAX 40K to a five-Engine VMAX 40K. How many new vault devices will be added as a result of this upgrade?

A. 32		
B. 40		
C. 64		
D. 80		
Correct Answer: A		

QUESTION 2

A director replacement is required on VMAX 20K. The customer asks what the impact will be on the front-end ports of the director being replaced. What should your response be?

- A. The front-end I/O modules will go offline.
- B. The front-end I/O modules will use a redundant Virtual Matrix.
- C. The front-end I/O modules will use redundant SIB.
- D. The front-end I/O modules will remain online.

Correct Answer: A

QUESTION 3

A CE is dispatched to replace a Drive. After logging into a Symmetrix VMAX 40K running Enginuity 5876.159.102 Simplified SymmWin is automatically launched. How should the CE proceed?

- A. Select Service Request Number then click Run Task
- B. Close Simplified SymmWin and select SymmWin from the desk top, then select Procedure Wizard
- C. Log off then log on using a Break Fix Credential
- D. Simplified SymmWin does not support VMAX 40K

Correct Answer: A

QUESTION 4

Which Enginuity version introduced Simplified Symmwin?



- A. 5876
- B. 5875
- C. 5773
- D. 5772
- Correct Answer: A

What is the EMC recommended best practice when configuring a volume on a VMAX 10K?

- A. Configured as a THIN device
- B. Configured as a THICK device
- C. Configured as an SRDF device
- D. Configured as a DSE device

Correct Answer: A

QUESTION 6

What is a characteristic of VMAX 20K Power Vault Hypers (PVDs)?

- A. PVDs are 5 GB in size.
- B. There are two PVDs per physical disk drive.
- C. Space is allocated for PVDs in Global Memory.
- D. There are four PVDs per physical disk drive.

Correct Answer: A

QUESTION 7

What is the maximum number of 3.5 inch drives that can be configured in a Symmetrix VMAX 20K?

- A. 2400
- B. 3200
- C. 1080
- D. 1560
- Correct Answer: A



What is the maximum number of drives that can be configured in a Symmetrix VMAX 10K (959)/VMAXe with Standard DAE configuration?

- A. 3200 B. 2400 C. 1560
- D. 1080

Correct Answer: D

QUESTION 9

Which SRDF operation results in a suspended link?

- A. Split
- B. Swap
- C. Failback
- D. Restore
- Correct Answer: A

QUESTION 10

In a cascaded SRDF/EDP configuration, which device type is used as a cache only device?

- A. R21
- B. R22
- C. R11
- D. Standard Clone
- Correct Answer: A

QUESTION 11

Which component types are installed in a VMAX 10K Storage Bay?

A. DAE, PDP, PDU, LCC



B. DAE, PDP, PDU, SPS

C. LCC, SPS, PDP, PDU

D. DAE, FAN, PDU, SPS

Correct Answer: A

QUESTION 12

What is the maximum distance for System Bay Dispersion in a VMAX 40K configuration?

- A. 82.0 feet/25m
- B. 32.8 feet/10m
- C. 16.4 feet/5m
- D. 49.2 feet/15m
- Correct Answer: A

QUESTION 13

Which set of VMAX interface types support software compression with SRDF?

- A. FC and 10 GigE
- B. FCoE and FC
- C. 10 GigE and FCoE
- D. Ficon and 10 GigE

Correct Answer: A

QUESTION 14

What is the default folder where SymmWin 5876 is installed?

- A. C:\SymmWin
- B. C:\Program files\EMC\SymmWin\5876
- C. C:\SymmWin\5876
- D. C:\Program files\EMC\SymmWin

Correct Answer: A



Which VMAX Models Support CKD Virtual Provisioning?

- A. VMAX 40K and VMAX 20K
- B. VMAX 40K, VMAX 20K and VMAX 10K
- C. VMAX 10K and VMAX 40K
- D. VMAX 10K and VMAX 20K

Correct Answer: A

E20-616 PDF Dumps

E20-616 Exam Questions

E20-616 Braindumps