

HH0-210^{Q&As}

HDS Certified Implmenter-Enterprise

Pass Hitachi HH0-210 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.certbus.com/hh0-210.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

A customer wants to install an Emulex HBA in a server accessing storage in a Hitachi VSP system. Where can you verify that the given configuration is supported?

- A. VSP maintenance manual
- B. HDS HBA implementation guide
- C. Storage Navigator User's Guide
- D. HiFire on HDS intranet/extranet

Correct Answer: D

QUESTION 2

With which two products does Hitachi Tuning Manager integrate? (Choose two.)

- A. Device Manager
- B. Protection Manager
- C. Replication Manager
- D. Tiered Storage Manager

Correct Answer: AD

QUESTION 3

A customer is using the Hitachi Command Suite for their VSP environment.

Which tab in the GUI provides the Hitachi Tiered Storage Manager volume migration functionality?

- A. the Analytics tab
- B. the Mobility tab
- C. the Migrator tab
- D. the Tiering tab

Correct Answer: B

QUESTION 4

A customer wants to suppress page migration for a certain Hitachi Dynamic Tiering volume on a VSP. How can this be done?

- A. by setting Multi-Tier Pool to Disable
- B. by setting Tier Management to Auto
- C. by setting Tier Relocation to Disable
- D. by setting the Cycle Time to 24 hours

Correct Answer: C

QUESTION 5

Which three steps should be performed during a new VSP installation? (Choose three.)

- A. Install HiTrack Monitor on a customer server and configure it.
- B. Set the battery date for each battery.
- C. Install all SSVP jumpers.
- D. Connect the CE laptop to the Console LAN connection port on the SVP.
- E. Dump the final configuration and upload it to TUF.

Correct Answer: BDE

QUESTION 6

Which two components are part of the VSP HiStar-E architecture? (Choose two.)

- A. MCH
- B. BED
- C. HDD
- D. SVP

Correct Answer: AB

QUESTION 7

A VSP customer is attaching new SUSE Linux servers to their SAN. What are two configuration requirements? (Choose two.)

- A. The queue depth per VSP LUN must not exceed 32.
- B. The queue depth per VSP LUN must be at least 8.
- C. The queue depth per VSP port must not exceed 2048.
- D. The queue depth per VSP port must not exceed 1024.

Correct Answer: AC

QUESTION 8

What is the purpose of the System Assurance Document?

- A. to ensure accurate and complete record of pre-installation data
- B. to guarantee that HDS equipment is insured during transportation
- C. to inform a channel partner that equipment is available for shipment
- D. to validate configuration changes for customers with a premium service contract

Correct Answer: A

QUESTION 9

A customer has virtualized a USP behind a VSP.

Which two actions can be performed by Universal Volume Manager? (Choose two.)

- A. configure load balancing by path group
- B. set the cache mode for the external volumes
- C. migrate USP volumes to the VSP
- D. expand external volumes

Correct Answer: AB

QUESTION 10

An application running on a Windows server connected to a Hitachi Enterprise storage system with two paths is generating mostly sequential I/O.

Which algorithm should be set in Hitachi Dynamic Link Manager (HDLM) on that server?

- A. Least Blocks
- B. Round Robin
- C. Sequential Blocks
- D. Extended Least I/Os

Correct Answer: D

QUESTION 11

A VSP customer is attaching new SUSE Linux servers to their SAN. What are two configuration requirements? (Choose two.)

- A. The queue depth per VSP LUN must not exceed 32.
- B. The queue depth per VSP LUN must be at least 8.
- C. The queue depth per VSP port must not exceed 2048.
- D. The queue depth per VSP port must not exceed 1024.

Correct Answer: AC

QUESTION 12

A customer wants to de-install a USP which is currently virtualized behind a VSP. They have stopped the Host I/O to the affected LUNs and have unmounted them. What is the next sequence?

- A. Delete LUN Paths > power off the USP
- B. Switch off cache mode for the external volumes > power off the USP
- C. Perform Disconnect External Storage for the USP > disconnect the external volumes > power off the USP
- D. Delete LUN Paths > perform Disconnect External Storage for the USP > delete the external volumes > power off the USP

Correct Answer: D

QUESTION 13

Which VSP component owns an LDEV?

- A. Front-end Director
- B. Virtual Storage Director
- C. Back-end Director
- D. Cache

Correct Answer: B

QUESTION 14

A customer is using a Hitachi Enterprise storage system with clustered servers in an active/passive relationship.

What must be done in Hitachi Dynamic Link Manager (HDLM) to ensure that the status of inactive paths on both passive and active nodes is monitored regularly?

- A. Switch on Auto Failback.
- B. Switch on Path Health Check.
- C. Set the reservation level to 2.
- D. Set up Intermittent Error Monitoring.

Correct Answer: B

QUESTION 15

A customer wants to add a second DKC to a VSP.

Which three hardware features must be installed in the second DKC? (Choose three.)

- A. Hub
- B. VSD
- C. CMA
- D. ESW
- E. DKA

Correct Answer: ABD

[Latest HH0-210 Dumps](#)

[HH0-210 PDF Dumps](#)

[HH0-210 Exam Questions](#)