

# HH0-450<sup>Q&As</sup>

Hitachi Data Systems Storage Architect-Hitachi NAS Platform

## Pass Hitachi HH0-450 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.certbus.com/hh0-450.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Hitachi  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



### QUESTION 1

Your customer is using iSCSI LUNs on a Hitachi NAS Platform. Which three Hitachi NAS file system management functions will the customer be able to use? (Choose three.)

- A. snapshots
- B. SnapMirror
- C. NVRAM logging
- D. iLUN expansion
- E. Quotas

Correct Answer: ACE

---

### QUESTION 2

A customer has a mixed UNIX and Windows environment and they are planning to implement a Hitachi NAS Platform. Which three host name resolution methods are supported in this environment? (Choose three.)

- A. WINS
- B. NTP
- C. DNS
- D. NDS
- E. NIS

Correct Answer: ACE

---

### QUESTION 3

The administrator of a Hitachi NAS Platform wants to automate the replication of a directory called "Finance" within the file system called "accounts". Other data in this file system should not be replicated. Which product should be used to achieve this?

- A. Hitachi TrueCopy (TC)
- B. Hitachi Universal Replicator (HUR)
- C. Incremental Data Replication
- D. Data Migration

Correct Answer: C

---

#### QUESTION 4

You are creating a deployment plan for a new Hitachi NAS Platform customer that will meet their recovery and data consolidation requirements for their NFS and CIFS data. Which two key infrastructure areas must you identify for the design? (Choose two.)

- A. Recovery Point Objective
- B. types of servers
- C. Recovery Time Objective
- D. number of NDS servers

Correct Answer: AC

---

#### QUESTION 5

The administrator of a production Hitachi NAS Platform requires integration to their backup platform. Which two configurations are supported? (Choose two.)

- A. direct tape connectivity
- B. serverless backup
- C. NDMP v4 backup over the LAN
- D. block level backup direct to tape

Correct Answer: AC

---

#### QUESTION 6

A customer has purchased a 2-node Hitachi NAS platform 3080 cluster. The customer would like to optimize the design of their network for Windows clients accessing files stored on the 3080. Which three factors must be considered? (Choose three.)

- A. the number of anti-virus scanning servers with the 3080
- B. the make and model of the customer Fibre Channel switches
- C. the current and planned use of VLANs
- D. the use of clustered read caching
- E. the use of 1 GbE versus 10 GbE connections from the 3080

Correct Answer: ACE

---

#### QUESTION 7

A customer wants to install the two nodes of a Hitachi NAS Platform cluster 125 meters apart. What are two prerequisites? (Choose two.)

- A. The cluster interconnect XFPs must be longwave laser extended.
- B. The multimode fiber optic media must comply with the OM3 standard.
- C. A DWDM is required.
- D. The SMU containing the Quorum must have network access to both nodes.

Correct Answer: BD

---

#### QUESTION 8

When planning for the installation of a Hitachi NAS platform MetroCluster, which three Hitachi Data Systems documents must be completed? (Choose three.)

- A. Pre-Engagement Checklist
- B. Systems Assurance Document
- C. Remote Copy Planning and Design Pre-Qualification Questionnaire
- D. Site Implementation Guide
- E. Change Control Approval Form

Correct Answer: ABC

---

#### QUESTION 9

A customer plans to implement HiTrack Monitoring for their Hitachi NAS Platform from the customer's management LAN. Which two are needed? (Choose two.)

- A. a configured SMTP server
- B. a configured SNMP community string
- C. Admin-EVS accessible from the customer's management LAN
- D. an enabled HTTPS certificate

Correct Answer: BC

---

#### QUESTION 10

A customer would like to manage quotas at the directory level on a Hitachi NAS Platform. What would you recommend to the customer?

- A. Virtual Directories

- B. Virtual Volumes
- C. Quota Tree
- D. Sparse Directories

Correct Answer: B

---

#### QUESTION 11

A customer would like to implement a 2-node Hitachi NAS Platform 3080 cluster using a Hitachi AMS2100 storage system. The AMS2100 is shared with other Open Systems platforms. Ports 0B and 1B are the only ports available in the AMS2100. Hport 1 and 3 are the only ports available on the Hitachi NAS Platform nodes. Which two wiring and zoning configurations should be used? (Choose two.)

- A. Hport 1 of both nodes, and AMS port 0B must be connected to switch 1 and could be in the same zone.
- B. Hport 1 and 3 of node 1, and AMS port 0B must be connected to switch 1 and could be in the same zone.
- C. Hport 3 of both nodes, and AMS port 1B must be connected to switch 2 and could be in the same zone.
- D. Hport 1 and 3 of node 2, and AMS port 1B must be connected to switch 2 and could be in the same zone.

Correct Answer: AC

---

#### QUESTION 12

A customer has just implemented anti-virus scanning on their Hitachi NAS Platform and they are experiencing degraded performance since the implementation. Which three actions can the customer take to improve performance? (Choose three.)

- A. Increase the number of anti-virus scanning servers.
- B. Enable SMB signing to reduce protocol overhead.
- C. Upgrade the anti-virus scanning servers to a higher performance class.
- D. Optimize the network connectivity between the anti-virus scanning servers and the Hitachi NAS Platform.
- E. Enable ICMP on the anti-virus scanning servers.

Correct Answer: ACD

---

#### QUESTION 13

A customer plans to have over 30 network clients accessing their Hitachi NAS Platform. They would like to increase their bandwidth by combining multiple network ports on a single Cisco switch. Which protocol do they need to configure on the switch?

- A. Link Aggregate Control Protocol (LACP 802.3ad)

- B. Port Aggregation Protocol (PAgP)
- C. Multiprotocol Label Switching (MPLS)
- D. Multi Link Trunk (MLT)

Correct Answer: B

---

#### QUESTION 14

When configuring iSCSI initiators, which two must be configured to facilitate dynamic target (server) discovery from the Hitachi NAS platform? (Choose two.)

- A. the iSCSI LUN
- B. the iSCSI target portal
- C. the iSCSI IQN
- D. the iSNS

Correct Answer: BD

---

#### QUESTION 15

A customer would like to implement a Hitachi NAS Platform in a NFS environment. They have two business requirements: 1. "Dev" department workload is write intensive random workload and requires excellent performance. 2. "Eng" department workload is 80% read and 20% write random workload and requires a right balance between cost and performance. Which RAID group type should you choose?

- A. RAID-10 for Dev and RAID-DP for Eng
- B. RAID-5 for Dev and RAID-10 for Eng
- C. RAID-10 for Dev and RAID-5 for Eng
- D. RAID-10 for Dev and RAID-1 for Eng

Correct Answer: C

[HH0-450 Practice Test](#)

[HH0-450 Study Guide](#)

[HH0-450 Exam Questions](#)