www.CertBus.com

HP2-T23^{Q&As}

Supporting Industry Standard Server Solutions

Pass HP HP2-T23 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.certbus.com/hp2-t23.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by HP Official
Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Which HP tool is used to configure NIC teaming on a Windows server?

A. ORCA

B. Insight Control

C. PCM+

D. RBSU

Correct Answer: B

QUESTION 2

An administrator needs to extend the runtimes for a company\\\'s critical devices in case of utility power failure.

Which HP management software should the administrator use to configure the power failure settings on the company\\\'s HP UPS?

A. HP Systems Insight Manager HP SIM)

B. HP UPS Power Protecting Agents

C. HP Power Protector

D. HP Insight Power Control

Correct Answer: C

QUESTION 3

An engineer is installing an HP R7000 UPS and an Extended Runtime Module (ERM) in an existing HP 10642 G2 rack. This rack contains 10 ProLiant DL380e Gen8 servers mounted from 1U upward.

How should the engineer perform this installation?

A. Mount the R7000 UPS at 10U in the 10642 G2 rack with the ERM on top of the R7000 UPS.

B. Remove the lowest ProLiant DL380e Gen8 servers and mount the R7000 and the ERM at the lowest position in the rack. Mount the removed ProLiant DL380e Gen8 servers at a higher position in the 10642 G2 rack.

C. Mount the R7000 at the highest position possible in the 10642 G2 rack with the ERM just below the UPS.

D. Remove the two lowest mounted ProLiant DL380e Gen8 servers and mount the R7000 at the bottom of the 10642 G2 rack. Mount the two removed ProLiant DL380e Gen8 servers at the top of the 10642 G2 rack. Mount the ERM above the remaining original mounted ProLiant DL380e Gen8 servers.

Correct Answer: B

QUESTION 4

An engineer repaired a memory problem in a ProLiant BL460c Gen8 server blade running Windows 2008 R2. What should the engineer do to verify the repair? (Select two.)

A. Observe the Insight Display at the front of the server after it boots.

B. Check the Active Health System.

C. Observe the server console for POST errors.

D. Reboot the BL460c Gen8 server and run the offline Insight Diagnostics.

E. Reseat the memory and inform the customer when the job is done.

Correct Answer: AD

QUESTION 5

To boot a USB firmware memory key built by the HP USB key utility, where should an engineer insert the key to upgrade the firmware on the server blade?

A. Redundant Onboard Administrator USB connector

B. Onboard Administrator USB port

C. USB key on the server blade

D. SUV cable USB connector

Correct Answer: B

QUESTION 6

How many months is the support duration for a Service Pack for ProLiant versions release?

A. 6

B. 12

C. 18

D. 24

Correct Answer: B

QUESTION 7

Which software tool should you use to deploy an operating system to a ProLiant BL460c Gen8 server blade?

A. System Management Homepage

B. Array Configuration Utility

C. SmartStart

D. Intelligent Provisioning

Correct Answer: D

QUESTION 8

Which host management solution does HP recommend using with ProLiant Gen8 servers?

A. SNMP Agents

B. Agentless Management Service (AMS)

C. WBEM providers

D. Windows Management Instrumentation (WMI)

Correct Answer: B

QUESTION 9

Which statement describes the features of Service Pack for ProLiant (SPP)?

A. SPP is a combination of the PSPs and the HP SmartUpdate Firmware DVD.

B. SPP requires configuration through RBSU.

C. SPP is the replacement for the Service and Diagnostics tools.

D. SPP is supported only on servers running a Windows operating system.

Correct Answer: C

QUESTION 10

Why should you use an electrostatic discharge (ESD) wrist strap when replacing parts such as memory DIMMs?

A. A 48 V DC PSU will contribute to higher static electricity.

B. It incorporates high resistance and dissipates electrical charges into the ozone.

C. A current of more than 75 mA can kill someone.

D. It prevents the part from being damaged by static electricity.

Correct Answer: D

QUESTION 11

Which hardware-based system security feature can securely store information such as passwords and encryption keys and can be used to authenticate the platform?

A. DHCP

B. RBSU

C. ORCA

D. TPM

Correct Answer: D

QUESTION 12

What happens if you lose or misplace a Trusted Platform Module (TPM) key?

A. The system requests the Administrator password.

B. The system enters diagnostic mode.

C. The system will not boot.

D. Data loss might occur.

Correct Answer: D

QUESTION 13

What should an administrator do to prevent discharge of static electricity when replacing components in a ProLiant server? (Select two.)

A. Place the server blade on a flat, level surface.

B. Wear a plastic grounding strap to remove the ESD-sensitive component from the static safe container

C. Place the ESD-sensitive component on a grounded surface.

D. Wear a cloth grounding strap to replace the defective component.

E. Avoid hand contact with the ESD-sensitive component by transporting in a static-safe container.

Correct Answer: BE

QUESTION 14

What should a system administrator use to save an enclosure backup?

A. HP One Button Disaster Recovery (OBDR)

B. SmartStart Scripting Toolkit

C. Amirrored drive

D. Aconfiguration script

Correct Answer: D

QUESTION 15

A ProLiant DL380 Gen8 ser/er has become unresponsive several times during the last two weeks You contacted HP Technical Support and were asked to send them the Active Health System log for the last two weeks Where can you download this log? [Select two.)

A. Array Configuration Utility (ACU)

B. iLO infoimatioi page

C. Integrated Management log (IML)

D. Intelligent Provisioning Maintenance page

E. ROM Based Setup Utility (RBSU)

Correct Answer: BD

[Latest HP2-T23 Dumps](#)   [HP2-T23 Exam Questions](#)   [HP2-T23 Braindumps](#)