

MA0-101^{Q&As}

McAfee Certified Product Specialist - NSP

Pass McAfee MA0-101 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.certbus.com/ma0-101.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by McAfee
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



QUESTION 1

In L3 mode, a sensor detects an L2 device based on which address?

- A. MAC
- B. IP
- C. Default Gateway
- D. DNS

Correct Answer: B

QUESTION 2

Which attack cannot be blocked when the sensor has been set for in-line mode?

- A. TCP Control Anomaly
- B. ICMP Echo Anomaly
- C. Too Many Inbound Syn
- D. SCADA Attacks

Correct Answer: A

QUESTION 3

Which port is correctly defined for the Alert Channel on the Network Security Manager?

- A. 8500
- B. 8501
- C. 8502
- D. 8504

Correct Answer: C

QUESTION 4

Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method?

- A. Signature based

- B. Pattern matching
- C. Denial of Service
- D. Remediation

Correct Answer: C

QUESTION 5

_____ are required to be configured before configuring the quarantine/pre-admission user classes or the quarantine DHCP server.

- A. Integrated DHCP servers
- B. Wild Card DNS servers
- C. Wins Servers
- D. Portal Servers

Correct Answer: B

QUESTION 6

Which of the following actions can a Standby Manager of an MDR pair perform?

- A. Modify sensor configuration
- B. Policy configuration
- C. Signature update
- D. Configuration backup

Correct Answer: D

QUESTION 7

Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?

- A. sensor perf-debug 100
- B. sensor perf-debug on 100
- C. sensor perf-debug Interface all 100
- D. sensor perf-debug assert 100

Correct Answer: A

QUESTION 8

Which CLI command is used to determine that the Sensor has established trust with the Manager?

- A. config
- B. status
- C. trust
- D. show

Correct Answer: B

QUESTION 9

Which command allows an off-line signature file download from a tftp server when connectivity to the Manager is unavailable?

- A. Loadimage
- B. Loadconfig
- C. Loadconfiguration
- D. Loadsigset

Correct Answer: C

QUESTION 10

Where in the Network Security Manager console can you see a hierarchical view of all the installed applications currently deployed and the resources associated with each?

- A. Device List
- B. Resource Tree
- C. Details Pane
- D. System Links

Correct Answer: A

QUESTION 11

Reconnaissance Policies can be applied to which of the following sensor nodes?

- A. Sensor name node only

- B. Sensor interface node only
- C. Sensor sub-interface node only
- D. Sensor name, interface and sub-interface node

Correct Answer: A

QUESTION 12

Which of the following are the methods used by NSP to recognize and react to Denial-of-Service (DoS) attacks?
(Choose three)

- A. Blocking
- B. Shutting down the sensor
- C. Thresholds
- D. Self-learning
- E. Logging
- F. DDoS attack tool with exploit signatures

Correct Answer: CDF

QUESTION 13

When McAfee NAC reports the host status as unmanaged with an Unknown Health Level, the sensor redirects the host to which of the following?

- A. Guest Client Portal
- B. NAC Client Portal
- C. Sensor Client Portal
- D. DNS Server Portal

Correct Answer: A

QUESTION 14

As a recommended best practice, what is the total number of sensors that should be managed through a single Network Security Manager installation?

- A. 25
- B. 50

C. 75

D. 100

Correct Answer: B

QUESTION 15

What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?

A. arp spoof status

B. arp spoof enable

C. arp dump

D. arp flush

Correct Answer: C

[MA0-101 PDF Dumps](#)

[MA0-101 VCE Dumps](#)

[MA0-101 Braindumps](#)